



CENNTRO

TEEMAK

TECHNICAL SPECIFICATIONS*

ALL-ELECTRICAL, PURPOSE-BUILT AS OFF-ROAD UTILITY TASK VEHICLE

With its extroverted look, the Teemak shows where it feels at home - off the mainstream roads on more or less paved paths and inclines.

- **PAYLOAD**

1000 kg payload

- **VEHICLE CLASSIFICATION**

L&F (Agriculture & Forestry)

- **CHARGING AND LONG RANGE**

AC charge 8h (230V); 75 km at full charge

- **HIGHLIGHT FEATURES**

Electronic power steering (EPS), Central drivers display, Roof-mounted headlamps (optional), Winch, Electronic brakeforce distribution (EBD), Electric heating system, LED headlamps

● 1-ton-payload
● 25 % slope
● 75 km

BASIC INFORMATION

Vehicle Size (L x W x H)	4010 x 1600 x 2150 mm
Flatbed Size (L x W x H)	1970 x 1560 x 400 mm
Wheel Base	2500 mm
Minimum Ground clearance	200 mm
Curb Weight	1100 kg
Gross Weight	2100 kg
Payload	1000 kg
Towing capacity	1000 kg

* Technical as well as equipment changes are reserved. All information on Cenntro products corresponds to the status on the day of publication. Errors and mistakes cannot be totally excluded.



TEEMAK

TECHNICAL SPECIFICATIONS*

PERFORMANCE

Max. Speed	55 km/h
Grade Ability	25 %
Max Range of Pure Electricity	75 km
Peak Torque	105 Nm
Rated/Peak Power	7,5/15 kW



ELECTRIC SYSTEM

Battery	LiFePO4 (11,5 kWh)
AC Charging capacity	max. 1,4 kW, 8 hours
Drive	Rear



FOLLOW US

